



# Ultraprime

## Product Data Sheet

### **DESCRIPTION:**

ULTRAPRIME is a single component penetrating moisture cure concrete sealer used with 5000 and 6000 products.

### **SUPPLEMENTAL PRODUCTS:**

All 5000 or 6000 flooring, lining, grout, and coating products.

### **PACKAGING AND COVERAGE:**

ULTRAPRIME is packaged in either a quart can, or a 2 gallon pail. Each two gallon kit will cover approximately 500 sq. ft. at 6 mils wet (3 mils DFT), depending on porosity of the concrete.

### **PREPARATION:**

See Installation Instruction Sheet for finish system to be installed.

### **MIXING:**

No mixing is required because ULTRAPRIME is a single component product.

### **APPLICATION:**

Apply ULTRAPRIME to the substrate surface with a roller in at approximately 6 mils wet (2 to 3 mils DFT). Make sure to wet entire surface, but do not allow ULTRAPRIME to puddle. Coverage will be approximately 250 sq. ft. per gallon at 6 mils wet (3 mils DFT). Working life of open container is 6-8 hours. Only apply ULTRAPRIME to surfaces you intend to lay within 6 hours. If left longer, the surface must be sanded or scarified.

### **CURE TIME:**

ULTRAPRIME will cure for application of finish product within 45 minutes at 75° F (24° C). Surface will be tacky when it is ready to be top-coated.

### **CLEANUP:**

Cured or hardened ULTRAPRIME will bond to practically all surfaces and is extremely difficult to remove. Clean all tools immediately after use with acetone or other solvent based cleaners.

### **SAFETY:**

Avoid skin contact. If eye contact occurs, flush with water and consult a physician immediately. Keep work areas well ventilated. Never seal a container as the continuing exothermic reaction may cause container to explode. ULTRAPRIME is manufactured using a solvent which will give off an odor during application. Customer is responsible for protecting employees and food products from these odors. Cured product poses no threat of odor contamination. ULTRAPRIME Material Safety Data Sheets are available upon request.

### **Limited Warranty**

Milamar Coatings products are manufactured to be free of defects in material and workmanship in meeting the properties specified on its individual Product Data Sheets. Users and installers of Milamar Coatings products are solely responsible for determining the suitability of the products for specific product applications. Milamar Coatings makes no Warranty or Guarantee, express or implied, including warranties of fitness, design compatibility or merchantability, for any particular use and shall have no responsibility or liability, including direct, indirect or consequential damages, due to injury, delay or third party claims for installation or repair. Likewise, Milamar Coatings assumes no liability of any nature for products that are adjusted in the field or that do not utilize all specified Milamar Coatings components. Should any Milamar Coatings product be proved to be defective within one year from the date of shipment, Milamar Coatings will, at its sole discretion, replace the material; issue a credit to the customer's account; or provide a cash refund for the initial, paid purchase price of the material. Potential claims regarding product quality must be received in writing by Milamar Coatings within 30 days of the discovery of such potential defect. This Warranty is exclusive of all other warranties, expressed or implied, and may only be adjusted in writing, signed by an officer of Milamar Coatings, L.L.C.

### **Milamar Coatings, L.L.C.**

[www.Milamar.com](http://www.Milamar.com)

311 NW 122nd Street, Ste. 100

Oklahoma City, OK 73114

Ph.: 405.755.8448

Fax: 405.755.8450