



FLOORING SITE ANALYSIS

Company Name _____ Date: _____
 Mailing Address: _____ Shipping Address: _____
 City: _____ State: _____ Zip: _____ Phone: _____ Fax: _____
 Contact(s): _____ Position: _____
 Type of Business: _____ Name of Areas: _____

EXPOSURE CONDITIONS

1. Flooring exposed to? Corrosion ☐ Wear ☐ Impact ☐ Water ☐ Oil & Grease ☐ Vibration ☐
Other: _____
2. Chemicals (concentrations & temperatures) _____
3. pH Range: From: _____ To: _____
4. Traffic: Foot: ☐ Cart: ☐ Truck: ☐ Weight: _____ Lbs.
Type of wheels: Steel ☐ Rubber ☐ Composition ☐ Size: _____
5. Imperfections: Chipped ☐ Rutted: ☐ Cracked: ☐ Other: _____
6. Structural Movement (Indicate on sketch) Control Joints _____ LF Expansion Joint _____ LF
7. How is floor cleaned? Water ☐ Temp _____ F Steam ☐ Other _____
8. Temperature of floor during production? _____ F Thermal Shock: Yes ☐ No ☐

DESCRIPTION OF APPLICATION

1. Dimensions: _____ Total Sq. Ft. _____
2. Coving: _____ LF Height: _____ Curb / Vertical: _____ LF Height: _____
3. Type of substrate: Concrete ☐ Steel ☐ Wood ☐ Other _____
4. Type of toppings to be removed: (Sq. Ft. / Thickness) Resinous flooring: ☐
Concrete Patch ☐ Paint ☐ Sealer ☐ Tile ☐ Asphalt ☐
Oil & Grease ☐ Metal ☐ Wood ☐ Other Toppings _____
5. Is substrate under topping: Sloped ☐ Flat ☐
6. Must drainage / pitch be established? (Explain estimated amount) _____
7. Surface conditions: Smooth: _____ % Small aggregate exposed: _____ Large aggregate exposed: _____
% _____
8. Age of floor: _____
9. Flooring system recommended: _____ Color: _____ Alternate: _____ Color: _____
10. What is the desired texture of the floor? _____

SITE /APPLICATION CONDITIONS

1. Job Access: Dock: _____ Ground Floor or Upper: _____ Freight elevator: _____
2. Area is: Indoor: ☐ Outdoor: ☐
3. Temperature of floor during installation and cure: _____ F _____ C

4. Obstructions (Explain in detail):
5. Work to be done: Weekday: Weekend: Holiday: Shutdown:
6. Total time available (hours) for application and cure. (Be specific):
7. Surface prep: Detergent scrub ☐ Shotblast ☐ Scarify ☐ Acid Etch ☐
8. Dust allowed: None ☐ Moderate: ☐ Heavy ☐
9. Removal (Sq. Ft.): Jackhammer Sq. Ft. Scabbler Sq. Ft. Other Sq. Ft.
10. Keying: Yes ☐ No ☐ Total Lineal Feet LF
11. Drains / Trenches (Number and Type)
12. Water available (Temp. and Pressure) F PSI
13. Compressed air available (Volume and Pressure) CFM PS
14. Electricity available: 110 V ☐ 220 V ☐ 220 V(3 ph 60 amp) ☐ 440 V (3 ph 60 amp) ☐
15. Lift truck available: Yes ☐ No ☐
16. Where can debris be disposed of ? On site Other
17. Solvent odor objectionable / ventilation required:
18. Safety requirements:
19. General notes:

Note: Please mark areas where floor is low. If not indicated, the flooring will follow the contour of the existing substance. Customer is responsible for protecting equipment and stopping all leaks that could effect adhesion or cure of flooring product.

DIAGRAM OF AREA

-----**FOR OFFICE USE ONLY**-----

Product Approved for Application

This is NOT an order

Customer Signature

Authorized Signature

Milamar Rep Signature

Milamar Coatings L.L.C.

311 NW 122nd Street | Suite 100 | Oklahoma City, OK 73114
Ph: 800-459-7659 | Fax: 405-755-8450 | www.milamar.com