FLOORINGS & LININGS A DIVISION OF MILAMAR COATINGS, L.L.C.

Material Safety Data Sheet

Revision Date:	08/12	Print Date:	08/21/12	
Version 2.0		MSDS Identification:	3300 Veil Coat - Part A	Epoxy Resin

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	:	3300 Veil Coat - Part A
Product Use Description	:	Epoxy Resin
Company	:	Protective Floorings and Linings A Division of Milamar Coatings, LLC 311 N.W. 122nd St, Suite 100 Oklahoma City, OK 73114
Telephone	:	405-755-8448
Emergency Telephone Number:		ChemTel 800-255-3924 or 813-248-0585 (International)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Weight)
Bisphenol A / Epichlorohydrin Resin	25068-38-6	65% - 85%
O-CRESYL GLYCIDYLETHER	2210-79-9	10% - 25%

3. HAZARDS INFORMATION

Emergency Overview Harmful If Swallowed Skin Sensitization May Cause Pulmonary Sensitization Eye Irritation Skin Irritation

4. FIRST AID MEASURES

Inhalation	: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
Skin Contact	: Remove contaminated clothing / shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until thoroughly cleaned. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.
Eye Contact	: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.

Revision Date: Version 2.0	08/12	Print Date: MSDS Identification:	08/21/12 3300 Veil Coat - Part A	Epoxy Resin
Ingestion			Do not induce vomiting. If vomiti prevent aspiration. Get medical	ng occurs spontaneously, keep head below hips to attention.
NOTES TO PHYSIC Symptoms	CIAN			ensitization (allergy) may be evidenced by rashes, ion (e.g., allergy, asthma) may be evidenced by h and cough.
Treatment			should be induced with supervision aspiration. If symptoms such as	een ingested and vomiting has not occurred, emesis on. Keep victim's head below hips to prevent loss of gag reflex, convulsions or unconsciousness ige using a cuffed endotracheal tube should be

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	:	Use water fog, "alcohol foam", dry chemical or carbon dioxide.
Specific Hazards During Fire Fighting	:	Material will not burn unless preheated.
Special Protective Equipment For Fire Fighters	:	Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots). Including a positive pressure NIOSH approved self-contained breathing apparatus.
Personal Precautions	:	May burn although not readily ignitable. Use cautious judgment when cleaning up large spills. Shut off leaks, if possible without personal risk.
Environmental Precautions	:	Dike and contain. Contain run-off and dispose of properly.
Clean-up Methods - Small Spillage	:	Take up with an absorbent material and dispose of properly.
Clean-up Methods - Large Spillage	:	Remove with vacuum trucks or pump to storage / salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue.
Additional advice	:	Notify authorities if any exposures to the general public or environment occurs or is likely to occur. See Section 13 for information on disposal.
6. ACCIDENTAL RELEASE MEASURES	:	(See Section 15 For Regulatory Information).
Protect People	:	Isolate area. Keep unnecessary and unprotected personnel from entering the area Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls / Personal Protection. Refer to Section 7, Handling, for additional precautionary measures.
Protect The Environment	:	Prevent from entering the soil, ditches, sewers, waterways and / or groundwater. See Section 12, Ecological Information.
Cleanup	:	Absorb with material such as sand. Collect in suitable and properly labeled containers. Remove residual with soap and hot water. Solvents are not

	Revision Date: Version 2.0	08/12	Print Date: MSDS Identification:		Epoxy Resin
				•	as the recommended exposure guidelines and safe c solvent are followed. Consult appropriate solvent nd exposure guidelines.
7. HANDLIN	G AND STORAGE	Ē			
	Handling		:	possibly cause pulmonary sensiti emptied, can contain hazardous soap and water before eating, dri facilities. Launder contaminated	if swallowed. May cause skin sensitization. May ization. Containers, even those that have been product residues. Minimize skin contact. Wash with inking, smoking, applying cosmetics, or using toile clothing before using. Contaminated leather articles, intaminated and should be destroyed to prevent
	Storage		:	Store in a cool, dry place with ad high temperatures.	equate ventilation. Keep away from open flames and

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Protective Measures	: Wear appropriate respirator and protective clothing
Engineering Measures	: Use ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.
Eye Protection	: Avoid contact with eyes. Wear chemical goggles if there is potential contact with eyes.
Skin And Body Protection	: Avoid prolonged or repeated contact with skin. Wear chemical-resistant gloves and other clothing as required to minimize contact.
Respiratory Protection	: Avoid breathing vapor or mists. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, Use either a full-face, atmosphere-supplying respirator or air purifying respirator for organic vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical State	:	Liquid.
Odor	:	Yellow.
Flash Point	:	> 93.33 degrees C (>199.99 degrees F) (Setaflash)
Vapor Pressure	:	Negligible.
Relative Density	:	1.14.
Relative Vapor Density	:	> 1.
Solubility In Water	:	Negligible.

	buildly Dula C				
	Revision Date: Version 2.0	08/12	Print Date: MSDS Identification:		Epoxy Resin
10. STABILI	TY AND REACTIN	VITY			
	Materials To Avoid		:	strong mineral and organic bas	g oxidizing agents, strong lewis or mineral acid, anc es, especially primary and secondary aliphatic amines. release with some curing agents.
	Hazardous Decomp	osition Proc	lucts :	Carbon monoxide, aldehydes, a	and acids may be formed during combustion.
	Hazardous Reaction	ns	:	Hazardous polymerization will r	not occur. Stable under normal use conditions.
11. TOXICO	LOGICAL INFOR	MATION			
	Acute Oral Toxicity		:	Expected to be of low toxicity, L	_D50 > 2000 mg/kg.
	Acute Dermal Toxic	tity	:	Expected to be of low toxicity, L	_D50 > 2000 mg/kg.
	Inhalation		:	-	oute of exposure, however, under conditions where possible, could cause respiratory tract irritation. May sitization.
	Skin		:		kin. Prolonged or repeated liquid contact can result in which may result in skin irritation and dermatitis. May
	Eyes		:	May be irritating to the eyes.	
	Ingestion		:	May be slightly toxic and may b	be harmful if swallowed.
	Aggravated Medica	I Condition	:		iratory disorders may be aggravated by exposure to or lung allergies may increase the chance of mptoms from exposure.
12. ECOLOO	GICAL INFORMA	TION			
	Biodegradability		:	This section will be updated as	ecological reviews are completed.
	Toxicity To Fish		:	This section will be updated as	ecological reviews are completed.
13. DISPOS	AL CONSIDERAT	TIONS			
	Product Disposal		:		e, it would not be a hazardous waste RCRA criteria ropriate disposal facility in compliance with local and

14. TRANSPORT INFORMATION

	Revision Date: 08/12 F Version 2.0 MSDS Ider	Print Date: ntification	
	CFR Proper Shipping Name Class UN / ID No. Packing Group	:	not regulated
15. REGUL/	ATORY INFORMATION		
	TSCA	:	All components listed.
	EINECS	:	All components are listed or exempt.
	DSL	:	All components listed.
	KECI (KR)	:	All components listed.
	PICCS (PH)	:	All components listed.
	ENCS (JP)	:	All components listed.
	INV (CN)	:	All components listed.
	AICS	:	All components listed.
	U.S. EPA CERCLA Hazardous Substances Bisphenol A / Epichlorohydrin Resin O-CRESYL GLYCIDYLETHER	s (40 CFR : :	R 302) No RQ No RQ
	Section 311 / 312	:	Acute Health Hazard
	U.S. EPA Emergency Planning and Comm (40 CFR 372.65) - Supplier Notification Rec Bisphenol A / Epichlorohydrin Resin O-CRESYL GLYCIDYLETHER		nt-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals No De minimis Concentration No De minimus Concentration
	U.S. EPA Emergency Planning and Commic (40 CFR 355, Appendix A).	unity Righ	ht-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance
	Bisphenol A / Epichlorohydrin Resin O-CRESYL GLYCIDYLETHER	:	Threshold Planning Quantity No TPQ Threshold Planning Quantity Not Listed
	Bisphenol A / Epichlorohydrin Resin O-CRESYL GLYCIDYLETHER	:	Reportable Quantity : No RQ Reportable Quantity Not Listed
	New Jersey Right-To-Know Chemical List Bisphenol A / Epichlorohydrin Resin O-CRESYL GLYCIDYLETHER	:	Not Listed Not Listed
	Additional Components Not Found in Section		Concentration Pemarks

Components	CAS - No.	Concentration	Remarks	
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed	

Revision Date: 08/12 Version 2.0	Print Date: MSDS Identification:	08/21/12 3300 Veil Coat - Part A	Epoxy Resin	
Pennsylvania Right-To-Know (Bisphenol A / Epichlorohydrin O-CRESYL GLYCIDYLETHEF	Resin :	Not Listed Not Listed		
O-ORESTE GETOIDTLETTIEF	· ·			
Additional Components Not Fo				
Components	CAS - No.	Concentration	Remarks	
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed	
O-CRESYL GLYCIDYLETHEF Additional Components Not Fo	ound In Section 2:	Not Listed	l Pemarka	_
Components	CAS - No.	Concentration	Remarks	
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed	
U.S. California Safe Drinking V Components	Vater & Toxic Enforcem	ent Act (Proposition 65) Addit Concentration	ional Components Not Found in Se Remarks	ection 2. Value
Phenyl Glycidyl Ether	< 5 PPM	U.S. California Safe Drinking Water And Toxic Enforcement Act (Proposition 65).	Not Listed	Listed: October 1 1990
HMIS Rating Healt Flammabilit				

16. OTHER INFORMATION

The information contained above is given in good faith based on the best data available at this time. No warranty, expressed or implied is made. User assumes full responsibility for determining appropriate use and application of the product. Consult PF&L, Inc. for further information.

:

Prepared By

Protective Floorings and Linings. EH&S Product Safety Department