PROJECTIVE FLOORINGS & LININGS A DIVISION OF MILAMAR COATINGS, L.L.C.

Material Safety Data Sheet

Revision Date:	08/12	Print Date:	08/21/12	
Version 2.0		MSDS Identification:	3300CT - Part A	Epoxy Resin

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name :	3300CT - Part A
Product Use Description :	Epoxy Resin
Company :	Protective Floorings and Linings A Division of Milamar Coatings, LLC 311 N.W. 122nd St, Suite 100 Oklahoma City, OK 73114
Telephone :	405-755-8448
Emergency Telephone Number:	ChemTel 800-255-3924 or 813-248-0585 (International)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Weight)
Bisphenol A / Epichlorohydrin Resin	25068-38-6	65% - 85%
O-CRESYL GLYCIDYLETHER	2210-79-9	10% - 25%

3. HAZARDS INFORMATION

Emergency Overview Harmful If Swallowed Skin Sensitization May Cause Pulmonary Sensitization Eye Irritation Skin Irritation

4. FIRST AID MEASURES

Inhalation	: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artific respiration if not breathing. Get medical attention.	cial
Skin Contact	: Remove contaminated clothing / shoes and wipe excess from skin. Flush skin w water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until thoroughly cleaned. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.	
Eye Contact	: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.	

Revision Date: Version 2.0	08/12	Print Date: MSDS Identification:	08/21/12 3300CT - Part A	Epoxy Resin
Ingestion			Do not induce vomiting. If vom prevent aspiration. Get medica	iting occurs spontaneously, keep head below hips to I attention.
NOTES TO PHYSIC Symptoms	CIAN			sensitization (allergy) may be evidenced by rashes, ation (e.g., allergy, asthma) may be evidenced by ath and cough.
Treatment			should be induced with supervisional aspiration. If symptoms such a	been ingested and vomiting has not occurred, emesis sion. Keep victim's head below hips to prevent s loss of gag reflex, convulsions or unconsciousness vage using a cuffed endotracheal tube should be

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	:	Use water fog, "alcohol foam", dry chemical or carbon dioxide.
Specific Hazards During Fire Fighting	:	Material will not burn unless preheated.
Special Protective Equipment For Fire Fighters	:	Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots). Including a positive pressure NIOSH approved self-contained breathing apparatus.
Personal Precautions	:	May burn although not readily ignitable. Use cautious judgment when cleaning up large spills. Shut off leaks, if possible without personal risk.
Environmental Precautions	:	Dike and contain. Contain run-off and dispose of properly.
Clean-up Methods - Small Spillage	:	Take up with an absorbent material and dispose of properly.
Clean-up Methods - Large Spillage	:	Remove with vacuum trucks or pump to storage / salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue.
Additional advice	:	Notify authorities if any exposures to the general public or environment occurs or is likely to occur. See Section 13 for information on disposal.
6. ACCIDENTAL RELEASE MEASURES	:	(See Section 15 For Regulatory Information).
Protect People	:	Isolate area. Keep unnecessary and unprotected personnel from entering the area Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls / Personal Protection. Refer to Section 7, Handling, for additional precautionary measures.
Protect The Environment	:	Prevent from entering the soil, ditches, sewers, waterways and / or groundwater. See Section 12, Ecological Information.
Cleanup	:	Absorb with material such as sand. Collect in suitable and properly labeled containers. Remove residual with soap and hot water. Solvents are not

	Revision Date: Version 2.0	08/12	Print Date: MSDS Identification:	***=***=	Epoxy Resin
				•	es the recommended exposure guidelines and safe c solvent are followed. Consult appropriate solvent nd exposure guidelines.
7. HANDLIN	G AND STORAGE	-			
	Handling		:	possibly cause pulmonary sensit emptied, can contain hazardous soap and water before eating, dr facilities. Launder contaminated	if swallowed. May cause skin sensitization. May ization. Containers, even those that have been product residues. Minimize skin contact. Wash with inking, smoking, applying cosmetics, or using toile clothing before using. Contaminated leather articles, ntaminated and should be destroyed to prevent
	Storage		:	Store in a cool, dry place with ad high temperatures.	equate ventilation. Keep away from open flames and

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Protective Measures	: Wear appropriate respirator and protective clothing
Engineering Measures	: Use ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.
Eye Protection	: Avoid contact with eyes. Wear chemical goggles if there is potential contact with eyes.
Skin And Body Protection	: Avoid prolonged or repeated contact with skin. Wear chemical-resistant gloves and other clothing as required to minimize contact.
Respiratory Protection	: Avoid breathing vapor or mists. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, Use either a full-face, atmosphere-supplying respirator or air purifying respirator for organic vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical State	:	Liquid.
Odor	:	Yellow.
Flash Point	:	> 93.33 degrees C (>199.99 degrees F) (Setaflash)
Vapor Pressure	:	Negligible.
Relative Density	:	1.14.
Relative Vapor Density	:	>1.
Solubility In Water	:	Negligible.

	Revision Date:	08/12	Print Date:						
	Version 2.0		MSDS Identification:	3300CT - Part A	Epoxy Resin				
10. STABILI	TY AND REACTI	VITY							
101 0 11 12 12 1	Materials To Avoid		:		ong oxidizing agents, strong lewis or mineral acid, anc ases, especially primary and secondary aliphatic amines.				
				Reacts with considerable heat release with some curing agents.					
	Hazardous Decom	position Pro	ducts :	Carbon monoxide, aldehydes, and acids may be formed during combustion.					
	Hazardous Reaction	ons	:	Hazardous polymerization wi	Il not occur. Stable under normal use conditions.				
11. TOXICO	LOGICAL INFOR	RMATION							
	Acute Oral Toxicity	1	:	Expected to be of low toxicity	∕, LD50 > 2000 mg/kg.				
	Acute Dermal Toxicity			Expected to be of low toxicity, LD50 > 2000 mg/kg.					
	Inhalation			Not expected to be a relevant route of exposure, however, under conditions where exposure to vapors or mists is possible, could cause respiratory tract irritation. May possibly cause pulmonary sensitization.					
	Skin		:	May be mildly irritating to the skin. Prolonged or repeated liquid contact can r defatting and drying of the skin which may result in skin irritation and dermatit cause skin sensitization.					
	Eyes		:	: May be irritating to the eyes.					
	Ingestion		:	May be slightly toxic and may	y be harmful if swallowed.				
Aggravated Medical Condition			:		spiratory disorders may be aggravated by exposure to n or lung allergies may increase the chance of symptoms from exposure.				
12. ECOLO	GICAL INFORMA	TION							
	Biodegradability		:	This section will be updated a	as ecological reviews are completed.				
	Toxicity To Fish		:	This section will be updated a	as ecological reviews are completed.				
13. DISPOS	AL CONSIDERA	TIONS							
	Product Disposal		:		aste, it would not be a hazardous waste RCRA criteria ppropriate disposal facility in compliance with local and				

14. TRANSPORT INFORMATION

	Revision Date Version 2.0	: 08/12	Print MSDS Identifi	Date: cation:		Epox	y Resin	
	CFR	Proper Shippir Class UN / ID No. Packing Group	-		not regulated			
15. REGULA	ATORY INFO	RMATION						
	TSCA			:	All components listed.			
	EINECS			:	All components are listed or exer	npt.		
	DSL			:	All components listed.			
	KECI (KR)			:	All components listed.			
	PICCS (PH)			:	All components listed.			
	ENCS (JP)			:	All components listed.			
	INV (CN)			:	All components listed.			
	AICS			:	All components listed.			
		CLA Hazardous) CFR				
		Epichlorohydrin F		:	No RQ No RQ			
			L. L					
	Section 311 / 3	512		:	Acute Health Hazard			
		ergency Planning 65) - Supplier No			t-To-Know Act (EPCRA) SARA	A Title	III Section 313 Toxic Chemicals	
	Bisphenol A / E	Epichlorohydrin F	Resin	:	No De minimis Concentration			
	O-CRESYL GI	LYCIDYLETHER		:	No De minimus Concentration			
	U.S. EPA Eme (40 CFR 355, /		and Communit	y Righ	t-To-Know Act (EPCRA) SARA	A Title	III Section 302 Extremely Hazardou	s Substance
		Epichlorohydrin f	Resin		Threshold Planning Quantity	•	No TPQ	
		LYCIDYLETHER		:	Threshold Planning Quantity	:	Not Listed	
	Bisphenol A / F	Epichlorohydrin F	Resin	:	Reportable Quantity		No RQ	
		LYCIDYLETHER		:	Reportable Quantity	•	Not Listed	
		ight-To-Know Ch						
		Epichlorohydrin F		:	Not Listed			
	U-URESTL GL		L .	•	Not Listed			
		nponents Not Fo				-		
	Components			`	Concentration	1	Pomarks	

Components	CAS - No.	Concentration	Remarks
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed

Revision Date: 0 Version 2.0	8/12	Print Date: MSDS Identification:	08/21/12 3300CT - Part A	Epoxy Resin	
Pennsylvania Right-To Bisphenol A / Epichlor O-CRESYL GLYCIDY	ohydrin R	esin :	Not Listed Not Listed		
Additional Component	s Not Fou				
Components		CAS - No.	Concentration	Remarks	
Phenyl Glycidyl Ether		122-60-1	< 5 PPM	Not Listed	
Additional Component	s Not Fou	nd In Section 2: CAS - No.	Concentration	Remarks	_
	s Not Fou		Concentration	Pomarks	
Phenyl Glycidyl Ether		122-60-1	< 5 PPM	Not Listed	
U.S. California Safe D Components	rinking Wa	ater & Toxic Enforcem	ent Act (Proposition 65) Addit Concentration	ional Components Not Found in S Remarks	ection 2. Value
Phenyl Glycidyl Ether		< 5 PPM	U.S. California Safe Drinking Water And Toxic Enforcement Act (Proposition 65).	Not Listed	Listed: October 1 1990
HMIS Rating	Health				
		4			
Flar	nmability Reactivity				

16. OTHER INFORMATION

The information contained above is given in good faith based on the best data available at this time. No warranty, expressed or implied is made. User assumes full responsibility for determining appropriate use and application of the product. Consult PF&L, Inc. for further information.

:

Prepared By

Protective Floorings and Linings. EH&S Product Safety Department