

Revision Date:	05/12	Print Date:	08/30/12	
Version 2.0		MSDS Identification:	3800FS - Part A	Epoxy Resin

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	:	3800FS - Part A
Product Use Description	:	Epoxy Resin
Company	:	Protective Floorings and Linings A Division of Milamar Coatings, LLC 311 N.W. 122nd St, Suite 100 Oklahoma City, OK 73114
Telephone	:	405-755-8448
Emergency Telephone Number	:	ChemTel 800-255-3924 or 813-248-0585 (International)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Weight)
Bisphenol A / Epichlorohydrin Resin	25068-38-6	65% - 85%
O-CRESYL GLYCIDYLETHER	2210-79-9	10% - 25%

3. HAZARDS INFORMATION

Emergency Overview Harmful If Swallowed Skin Sensitization May Cause Pulmonary Sensitization Eye Irritation Skin Irritation

4. FIRST AID MEASURES

Inhalation	: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
Skin Contact	: Remove contaminated clothing / shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until thoroughly cleaned. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.
Eye Contact	: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get medical attention.

Revision Date: Version 2.0	05/12	Print Date: MSDS Identification:	08/30/12 3800FS - Part A	Epoxy Resin
Ingestion			Do not induce vomiting. If vom prevent aspiration. Get medica	niting occurs spontaneously, keep head below hips to al attention.
NOTES TO PHYSIC Symptoms	CIAN			sensitization (allergy) may be evidenced by rashes, ation (e.g., allergy, asthma) may be evidenced by eath and cough.
Treatment			should be induced with supervi aspiration. If symptoms such a	been ingested and vomiting has not occurred, emesis ision. Keep victim's head below hips to prevent as loss of gag reflex, convulsions or unconsciousness vage using a cuffed endotracheal tube should be

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	:	Use water fog, "alcohol foam", dry chemical or carbon dioxide.
Specific Hazards During Fire Fighting	:	Material will not burn unless preheated.
Special Protective Equipment For Fire Fighters	:	Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots). Including a positive pressure NIOSH approved self-contained breathing apparatus
Personal Precautions	:	May burn although not readily ignitable. Use cautious judgment when cleaning up large spills. Shut off leaks, if possible without personal risk.
Environmental Precautions	:	Dike and contain. Contain run-off and dispose of properly.
Clean-up Methods - Small Spillage	:	Take up with an absorbent material and dispose of properly.
Clean-up Methods - Large Spillage	:	Remove with vacuum trucks or pump to storage / salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue.
Additional advice	:	Notify authorities if any exposures to the general public or environment occurs or is likely to occur. See Section 13 for information on disposal.
6. ACCIDENTAL RELEASE MEASURES	:	(See Section 15 For Regulatory Information).
Protect People	:	Isolate area. Keep unnecessary and unprotected personnel from entering the area Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls / Personal Protection. Refer to Section 7, Handling, for additional precautionary measures.
Protect The Environment	:	Prevent from entering the soil, ditches, sewers, waterways and / or groundwater. See Section 12, Ecological Information.
Cleanup	:	Absorb with material such as sand. Collect in suitable and properly labeled containers. Remove residual with soap and hot water. Solvents are not

	evision Date: /ersion 2.0	05/12	Print Date: MSDS Identification:	08/30/12 3800FS - Part A	Epoxy Resin
				•	ess the recommended exposure guidelines and safe fic solvent are followed. Consult appropriate solvent and exposure guidelines
7. HANDLING A	ND STORAGE				
Har	ndling			possibly cause pulmonary sens emptied, can contain hazardous soap and water before eating, c facilities. Launder contaminated	ic if swallowed. May cause skin sensitization. May itization. Containers, even those that have been s product residues. Minimize skin contact. Wash with Irinking, smoking, applying cosmetics, or using toile d clothing before using. Contaminated leather articles, ontaminated and should be destroyed to preven
Sto	prage			Store in a cool, dry place with a high temperatures.	dequate ventilation. Keep away from open flames and

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Protective Measures	: Wear appropriate respirator and protective clothing
Engineering Measures	: Use ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.
Eye Protection	: Avoid contact with eyes. Wear chemical goggles if there is potential contact with eyes.
Skin And Body Protection	: Avoid prolonged or repeated contact with skin. Wear chemical-resistant gloves and other clothing as required to minimize contact.
Respiratory Protection	: Avoid breathing vapor or mists. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, Use either a full-face, atmosphere-supplying respirator or air purifying respirator for organic vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical State	:	Liquid.
Odor	:	Yellow.
Flash Point	:	> 93.33 degrees C (>199.99 degrees F) (Setaflash)
Vapor Pressure	:	Negligible.
Relative Density	:	1.14.
Relative Vapor Density	:	> 1.
Solubility In Water	:	Negligible.

	Revision Date: Version 2.0	05/12	Print Date: MSDS Identification:	08/30/12 3800FS - Part A	Epoxy Resin		
10. STABILI	TY AND REACT	IVITY					
	Materials To Avoid	1	:	strong mineral and organic ba	ong oxidizing agents, strong lewis or mineral acid, anc ases, especially primary and secondary aliphatic amines. at release with some curing agents.		
	Hazardous Decom	position Pro	ducts :	Carbon monoxide, aldehydes, and acids may be formed during combustion			
	Hazardous Reaction	ons	:	Hazardous polymerization wi	Il not occur. Stable under normal use conditions.		
11. TOXICO	LOGICAL INFOR	RMATION					
	Acute Oral Toxicity	у	:	Expected to be of low toxicity	ι, LD50 > 2000 mg/kg.		
Acute Dermal Toxicity			:	Expected to be of low toxicity, LD50 > 2000 mg/kg.			
	Inhalation		:		t route of exposure, however, under conditions where is possible, could cause respiratory tract irritation. May ensitization.		
	Skin		:		skin. Prolonged or repeated liquid contact can result in in which may result in skin irritation and dermatitis. May		
	Eyes		:	May be irritating to the eyes.			
	Ingestion		:	May be slightly toxic and may	y be harmful if swallowed.		
Aggravated Medical Condition			:		spiratory disorders may be aggravated by exposure to n or lung allergies may increase the chance of symptoms from exposure.		
12. ECOLO	GICAL INFORMA	ATION					
	Biodegradability		:	This section will be updated a	as ecological reviews are completed.		
	Toxicity To Fish		:	This section will be updated a	as ecological reviews are completed.		
13. DISPOS	AL CONSIDERA	TIONS					
	Product Disposal		:		aste, it would not be a hazardous waste RCRA criteria ppropriate disposal facility in compliance with local and		

14. TRANSPORT INFORMATION

1	Revision Date: Version 2.0	05/12	Print MSDS Identific			Ерох	ky Resin	
(CFR	Proper Shippir Class UN / ID No. Packing Group	-	•	not regulated			
15. REGULAT	ory infor	RMATION						
Т	TSCA			:	All components listed.			
E	EINECS			:	All components are listed or exe	empt.		
Γ	DSL			:	All components listed.			
k	KECI (KR)			:	All components listed.			
F	PICCS (PH)			:	All components listed.			
E	ENCS (JP)			:	All components listed.			
I	NV (CN)			:	All components listed.			
ŀ	AICS			:	All components listed.			
E	Bisphenol A / E	CLA Hazardous pichlorohydrin I YCIDYLETHER			302) No RQ No RQ			
S	Section 311 / 3	12		:	Acute Health Hazard			
(E	(40 CFR 372.6 Bisphenol A / E		tification Require		t-To-Know Act (EPCRA) SAR No De minimis Concentration No De minimus Concentration	A Title	III Section 313 Toxic Chemicals	
(E	(40 CFR 355, A Bisphenol A / E		Resin	r Righ : :	t-To-Know Act (EPCRA) SAR Threshold Planning Quantity Threshold Planning Quantity	A Title :	III Section 302 Extremely Hazardous S No TPQ Not Listed	Substance
E	Bisphenol A / E	pichlorohydrin I YCIDYLETHER	Resin	:	Reportable Quantity Reportable Quantity	:	No RQ Not Listed	
E	Bisphenol A / E	ght-To-Know Ch pichlorohydrin I YCIDYLETHER	Resin	:	Not Listed Not Listed			
	Additional Com	ponents Not Fo	und in Section 2		Concentration		Pomarks	

Components	CAS - No.	Concentration	Remarks
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed

Revision Date: Version 2.0	05/12	Print Date: MSDS Identification:	08/30/12 3800FS - Part A	Epoxy Resin	
Pennsylvania Right-			N		
Bisphenol A / Epichl O-CRESYL GLYCID			Not Listed Not Listed		
Additional Compone	nts Not Fo				
Components		CAS - No.	Concentration	Remarks	_
Phenyl Glycidyl Ether		122-60-1	< 5 PPM	Not Listed	
Massachusetts Righ	t-To-Know	Chemical List.			
Bisphenol A / Epichl			Not Listed		
O-CRESYL GLYCIE	YLETHER	:	Not Listed		
Additional Compone	nts Not Fo				_
Components		CAS - No.	Concentration	Remarks	
Phenyl Glycidyl Ethe	er	122-60-1	< 5 PPM	Not Listed	
U.S. California Safe Components	Drinking W	/ater & Toxic Enforcem	ent Act (Proposition 65) Additi	ional Components Not Found in Se Remarks	ction 2.
Components		CONCENTIATION		Remarks	Value
Phenyl Glycidyl Ether		< 5 PPM	U.S. California Safe Drinking Water And Toxic Enforcement Act (Proposition 65).	Not Listed	Listed: October 1, 1990
HMIS Rating	Health Iammability			1	
	Reactivity				

16. OTHER INFORMATION

The information contained above is given in good faith based on the best data available at this time. No warranty, expressed or implied is made. User assumes full responsibility for determining appropriate use and application of the product. Consult PF&L, Inc. for further information.

:

Prepared By

Protective Floorings and Linings. EH&S Product Safety Department