# **MATERIAL SAFETY DATA SHEET**

# **SECTION I**

DATE OF PREPARATION June 2011

PRODUCT NAME: PRODUCT CLASS: PRODUCT TYPE: D.O.T. CATEGORY: ADDRESS:

# ICO Floor CoatingXT / OP FC

Epoxy Resin Part A 4.4-Isopropylidenediphenol Epichlorohydrin Resin Chemical, NOIBN International Coatings Div. of Milamar Coatings, L.L.C. 311 N.W. 122<sup>nd</sup> St. Ste. 100 Oklahoma City, OK 73114 405-755-8448 CHEM TEL 800-255-3924

TELEPHONE: EMERGENCY:

### **SECTION II - HAZARDOUS INGREDIENTS**

Listed below are the hazardous component(s) as defined in 49 CFR 172 and 29 CFR 1910 which are present in this product and all components which appear on the hazardous substance list of any state:

NONE

## **SECTION III - PHYSICAL DATA**

PHYSICAL STATE: SPECIFIC GRAVITY: DENSITY: PERCENT VOLATILES Moderate viscosity, amber liquid 1.69 at 77°F 14 lbs/gal 0 at 70°F

### **SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT:

200°F (Pensky Martens Closed Cup)

**EXTINGUISHING DATA:** Foam, Dry chemical, Carbon Dioxide (CO<sub>2</sub>) **NOTE:** Toxic fumes will be evolved when this material is involved in a fire. Self-contained breathing apparatus should be available for fire fighters. Cool fire-exposed containers with water.

# **SECTION V - HEALTH HAZARD DATA**

EFFECTS OF OVEREXPOSURE:						
ACUTE:	High concentrations of vapor cause irritation of eyes and respiratory tract. May cause					
	burns to skin and eyes. Liquid causes damage	to mucous membranes i	f swallowed.			
CHRONIC:	Prolonged or repeated exposure may cause as	sthma and skin sensitizat	ion or other			
	allergic response.					
EMERGENCY AND FIRST AID PROCEDURES:						
EYES:	Flush with water for at least 15 minutes, holding eyelids open. GET MEDICAL ATTENTION					
SKIN:	Wash thoroughly with water while removing contaminated clothing and shoes. Wash					
	clothing before re-use and discard contaminat	ed leather articles. GET N	IEDICAL ATTENTION			
	if effects such as swelling or reddening occur.					
INHALATION:	Remove to fresh air if effects occur and administer oxygen if necessary. GET MEDICAL					
	ATTENTION if effects persist.					
INGESTION:	GET MEDICAL ATTENTION IMMEDIATELY Do n	ot induce vomiting unless	s directed by physician.			
	SECTION VI - REACT					
STABILITY:	Stable under normal storage conditio	ns.				
INCOMPATIBIL	<b>NCOMPATIBILITY:</b> Avoid bringing into contact with strong oxidizing agents, and strong Lewis or					
Mineral acids						
HAZARDOUS DECOMPOSITION PRODUCTS:						
CO (Carbon Mo	noxide) CO <sub>2</sub> (Carbon Dioxide)	Acids	Aldehydes			

### **SECTION VII - SPILL OR LEAK PROCEDURE**

**IF MATERIAL IS SPILLED:** Avoid contact with material. Persons not wearing appropriate protective equipment (see below) should be excluded from the area of spill until clean-up is complete. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on clay, diatomaceous earth or other absorbent and shoveled into disposal containers.

**WASTE DISPOSAL METHOD:**This product, if disposed as shipped, is not a hazardous waste as specified on 40CFR261. Controlled incineration or buried landfill disposal should be in accordance with all Federal, State, and Local regulations.

## **SECTION VIII - SPECIAL PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** NIOSH approved respiratory protection required in the absence of proper environmental control. For emergencies, a self-contained breathing apparatus, or a full-face respirator is recommended.

**VENTILATION:** Local, except in confined space, e.g., tanks, in which case proper respiratory protection (see above) is required.

HAND PROTECTION: Impervious gloves, neoprene or rubber.

**EYE PROTECTION** Splash proof goggles or safety spectacles with side shields.

**OTHER PROTECTIVE EQUIPMENT:**Clean, body-covering clothing. Further safety equipment (apron, footwear, etc.) should be used as necessary to prevent contact with material.

### **SECTION IX - SPECIAL PRECAUTIONS**

- 1. Prevent all skin and eye contact.
- 2. Avoid breathing vapors.
- 3. Re-seal part used containers.
- 4. Ensure that all containers are properly labeled to prevent accidental ingestion.
- 5. Wash with soap and water before eating, drinking, smoking or using toilet facilities.
- 6. Observe conditions of good industrial hygiene and safe working practice.

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.

# **MATERIAL SAFETY DATA SHEET**

# **SECTION I**

### DATE OF PREPERATION June 2011

Exposure Limite

# PRODUCT NAME: ICO Floor Coating XT / OP FC PRODUCT CLASS: Epoxy Resin Hardener, Part B PRODUCT TYPE: Modified amines

Epoxy Resin Hardener, Part B Modified amines UN 1760 Corrosive liquid, N.O.S.(Amine Mixture) 8 PG III **International Coatings** Div. of Milamar Coatings, L.L.C. 311 N.W. 122<sup>nd</sup> St. Ste. 100 Oklahoma City, OK 73114 405-755-8448 CHEM TEL 800-255-3924

TELEPHONE: EMERGENCY:

D.O.T. CATEGORY:

ADDRESS:

**SECTION II - HAZARDOUS INGREDIENTS** 

					Exposure Limits	
Ingredient	CAS #	Maximum Content	TLV	PEL	<u>LD 50/ Ora</u> l	LD50/Dermal
Polyoxypropylene- diamine	9046-10-0	10%	NE	NE	1.6/kg	>60mg/kg
N- Aminoethyl Piperazine	140-31-8	40%	NE	NE	>2.3/kg	<2g/kg
1,2 - Cyclohexanediamine	694-83-7	5%	NE	NE	2.3/kg	NE

### **SECTION III - PHYSICAL DATA**

PHYSICAL STATE:	Low Viscosity, amber color
SPECIFIC GRAVITY:	1.03 at 77°F
DENSITY:	8.5 lbs/gal at 77° F
ODOR:	Slight ammoniated
VAPOR PRESSURE:	Less than 1 mm Hg @ 68°F
PERCENT VOLATILES:	0 AT 70°F

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA** 

FLASH POINT: LFL: UFL: >200°F (Setaflash Closed Cup) No data

No data

EXTINGUISHING MEDIA: Water fog, Alcohol Foam, CO<sub>2</sub>, Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Use a positive pressure, self-contained breathing apparatus.

Wear full protection coating.

Note: Will burn under right conditions of heat and oxygen supply.

# **SECTION V - HEALTH HAZARD DATA**

PERMISSABLE EXPOSU	RE LEVELS: NONE ESTABLISHED			
EFFECTS OF OVER EXPOSURE				
INHALATION	May cause nasal irritation, central nervous system depression or lung injury.			
EYES	This product can cause chemical burns to eyes. Eye damage may be irreversible.			
SKIN	May be corrosive or highly irritating to the skin. Repeated contact may cause sensitization and/or dermatitis.			
FIRST AID				
EYES	Flush with water for at least 15 minutes. GET MEDICAL ATTENTION			
SKIN	Wash thoroughly with water. Remove contaminated clothing and shoes. Wash clothing before re-use. Get medical attention if effects such as swelling or reddening occur.			
INHALATION	Remove to fresh air if effects occur and administer oxygen if necessary. <b>GET MEDICAL</b> ATTENTION.			
INGESTION	GET MEDICAL ATTENTION IMMEDIATELY. Do not induce vomiting unless directed by physician.			

# **SECTION VI - REACTIVITY DATA**

**STABILITY:** Stable under normal storage conditions.

**INCOMPATIBILITY:** Avoid bringing into contact with strong oxidizing agents, and strong Lewis or Mineral acids, bases

### HAZARDOUS DECOMPOSITION PRODUCTS:

CO (Carbon Monoxide)

CO<sub>2</sub> (Carbon Monoxide)

Acids

Aldehydes

## **SECTION VII - SPILL OR LEAK PROCEDURE**

### **STEPS TO TAKE IF SPILLED:**

Using adequate protective equipment, add dry material to absorb spill (if large spill, first dike to contain). Pick up and containerize. Flush area with dilute (5%) acetic acid. Collect rinsate for sewer or disposal.

## WASTE DISPOSAL:

This product, if disposed as shipped, is a hazardous waste as specified in 40 CFR 261 on the basis of its corrosivity. Consult state or local officials for proper disposal method.

### **SECTION VIII - SPECIAL PRECAUTION INFORMATION**

VENTILATION REQUIREMENTS Local, except if applied in confined spaces, where adequate respiratory protection is required.

PERSONAL PROTECTIVE EQUIPMENT RECOMMENDED FOR NORMAL USE CONDITIONS:

Eve protection: Chemical goggles. **SKIN PROTECTION:** Rubber or plastic gloves. Respirator with organic vapor cartridge N/A with local exhaust.

**RESPIRATORY PROTECTION:** 

## **SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep container tightly closed when not in use. Store in a dry location.

### **SECTION X - TRANSPORTATION**

**DOT PROPER NAME:** DOT HAZARD CLASSIFICATION OR DIVISION: **INDENTIFICATION NUMBER:** PACKAGING GROUP: LABELS REQUIRED:

Corrosive liquid, N.O.S. (Amine Mixture) 8 UN 1760 Ш

Corrosive

## SECTION XI – REGULATORY INFORMATION

WHMSIS CLASSIFICATION - Class E, Corrosive

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.