## **MATERIAL SAFETY DATA SHEET**

## **SECTION I**

DATE OF PREPARATION June 2011

ICO Floor Cove FC
Epoxy Resin Part A
4.4-Isopropylidenediphenol Epichlorohydrin Resin
Chemical, NOIBN
International Coatings
Div. of Milamar Coatings, L.L.C.
311 N.W. 122 <sup>nd</sup> St. Ste. 100
Oklahoma City, OK 73114
405-755-8448
CHEM TEL 800-255-3924

## **SECTION II - HAZARDOUS INGREDIENTS**

Listed below are the hazardous component(s) as defined in 49 CFR 172 and 29 CFR 1910 which are present in this product and all components which appear on the hazardous substance list of any state:

NONE

	SECTION III - PHYSICAL DATA
PHYSICAL STATE:	Moderate viscosity, amber liquid
SPECIFIC GRAVITY:	1.16 at 77°F
DENSITY:	9.7 lbs/gal
PERCENT VOALTILES:	0 at 70°F
_	SECTION IV - FIRE AND EXPLOSION HAZARD DATA
FLASH POINT:	200°F (Pensky Martens Closed Cup)

**EXTINGUISHING DATA:** Foam, Dry chemical, Carbon Dioxide (CO<sub>2</sub>)

**NOTE:** Toxic fumes will be evolved when this material is involved in a fire. Self-contained breathing apparatus should be available for fire fighters. Cool fire-exposed containers with water.

#### **SECTION V - HEALTH HAZARD DATA**

#### EFFECTS OF OVEREXPOSURE:

- ACUTE: High concentrations of vapor cause irritation of eyes and respiratory tract. May cause burns to skin and eyes. Liquid causes damage to mucous membranes if swallowed.
- **CHRONIC:** Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

#### **EMERGENCY AND FIRST AID PROCEDURES:**

 EYES:
 Flush with water for at least 15 minutes, holding eyelids open. GET MEDICAL ATTENTION.

 SKIN:
 Wash thoroughly with water while removing contaminated clothing and shoes. Wash clothing before re-use and discard contaminated leather articles. GET MEDICAL ATTENTION if effects such as swelling or reddening occur.

 INHALATION:
 Remove to fresh air if offects convert and administer environ if percessary. CET MEDICAL

**INHALATION:** Remove to fresh air if effects occur and administer oxygen if necessary. **GET MEDICAL ATTENTION** if effects persist.

**INGESTION:** GET MEDICAL ATTENTION IMMEDIATELY Do not induce vomiting unless directed by physician.

#### **SECTION VI - REACTIVITY DATA**

**STABILITY:** Stable under normal storage conditions.

**INCOMPATIBILITY:** Avoid bringing into contact with strong oxidizing agents, and strong Lewis or Mineral acids

#### HAZARDOUS DECOMPOSITION PRODUCTS:

CO( Carbon Monoxide)

CO<sub>2</sub> (Carbon Monoxide)

Acids

Aldehydes

## SECTION VII - SPILL OR LEAK PROCEDURE

**IF MATERIAL IS SPILLED:** Avoid contact with material. Persons not wearing appropriate protective equipment (see below) should be excluded from the area of spill until clean-up is complete. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on clay, diatomaceous earth or other absorbent and shoveled into disposal containers.

**WASTE DISPOSAL METHOD:** This product, if disposed as shipped, is not a hazardous waste as specified on 40CFR261. Controlled incineration or buried landfill disposal should be in accordance with all Federal, State, and Local regulations.

## **SECTION VIII - SPECIAL PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** NIOSH approved respiratory protection required in the absence of proper environmental control. For emergencies, a self-contained breathing apparatus, or a full-face respirator is recommended.

**VENTILATION:** Local, except in confined space, e.g., tanks, in which case proper respiratory protection (see above) is required.

HAND PROTECTION: Impervious gloves, neoprene or rubber.

**EYE PROTECTION:** Splash proof goggles or safety spectacles with side shields.

**OTHER PROTECTIVE EQUIPMENT:**Clean, body-covering clothing. Further safety equipment (apron, footwear, etc.) should be used as necessary to prevent contact with material.

## **SECTION IX - SPECIAL PRECAUTIONS**

- 1. Prevent all skin and eye contact.
- 2. Avoid breathing vapors.
- 3. Re-seal part used containers.
- 4. Ensure that **all** containers are properly labeled to prevent accidental ingestion.
- 5. Wash with soap and water before eating, drinking, smoking or using toilet facilities.
- 6. Observe conditions of good industrial hygiene and safe working practice.

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.

# **MATERIAL SAFETY DATA SHEET**

## **SECTION I**

DATE OF PREPERATION June 2011

PRODUCT NAME:	ICO Floor Cove FC
PRODUCT CLASS:	Epoxy Resin Hardener, Part B
PRODUCT TYPE:	Modified amines
D.O.T. CATEGORY:	UN 1760 Corrosive liquid, N.O.S. (Amine Mixture) 8 PG III
ADDRESS:	International Coatings
	Div. of Milamar Coatings, L.L.C.
	311 N.W. 122 <sup>nd</sup> St. Ste. 100
	Oklahoma City, OK 73114
TELEPHONE:	405-755-8448
EMERGENCY:	CHEM TEL 800-255-3924

#### **SECTION II - HAZARDOUS INGREDIENTS**

				Exposure Limits		
Ingredient	CAS #	Maximum Content	TLV	PEL	<u>LD 50/ Ora</u> l	LD50/Dermal
Polyoxypropylene- diamine	9046-10-0	10%	NE	NE	1.6/kg	>60mg/kg
N- Aminoethyl Piperazine	140-31-8	40%	NE	NE	>2.3/kg	<2g/kg
1,2 - Cyclohexanediamine	694-83-7	5%	NE	NE	2.3/kg	NE

SECTION	II - PHYSICAL DATA
SECTION	II- PHISICAL DATA

PHYSICAL STATE:
SPECIFIC GRAVITY:
DENSITY:
ODOR:
VAPOR PRESSURE:
PERCENT VOLATILES:

Low Viscosity, amber color 1.03 at 77°F 8.5 lbs/gal at 77° F Slight ammoniated Less than 1 mm Hg @ 68°F 0 AT 70°F

#### **SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT: LFL: UFL: EXTINGUISHING MEDIA: >200°F (Setaflash Closed Cup)

No data No data

Water fog, Alcohol Foam, CO<sub>2</sub>, Dry Chemical

**SPECIAL FIRE FIGHTING PROCEDURES:**Use a positive pressure, self-contained breathing apparatus. Wear full protection coating.

Note: Will burn under right conditions of heat and oxygen supply.

## **SECTION V - HEALTH HAZARD DATA**

PERMISSABLE EXPOSU	RE LEVELS: NONE ESTABLISHED
EFFECTS OF OVER EXPO	DSURE
INHALATION	May cause nasal irritation, central nervous system depression or lung injury.
EYES	This product can cause chemical burns to eyes. Eye damage may be irreversible.
SKIN	May be corrosive or highly irritating to the skin. Repeated contact may cause sensitization and/or dermatitis.
FIRST AID	
EYES	Flush with water for at least 15 minutes. GET MEDICAL ATTENTION
SKIN	Wash thoroughly with water. Remove contaminated clothing and shoes. Wash clothing before re-use. Get medical attention if effects such as swelling or reddening occur.
INHALATION	Remove to fresh air if effects occur and administer oxygen if necessary. GET MEDICAL ATTENTION.
INGESTION	GET MEDICAL ATTENTION IMMEDIATELY. Do not induce vomiting unless directed by physician.

	SECTION VI - REA	CTIVITY DAT	A	
STABILITY: Stable under normal sto	orage conditions.			
NCOMPATIBILITY: Avoid bringing in	nto contact with strong	oxidizing agent	s, and strong Lewis or Mineral	
acids, bases				
HAZARDOUS DECOMPOSITION PRO				
CO (Carbon Monoxide) CO2	(Carbon Monoxide)	Acids	Aldehydes	
SEC	TION VII - SPILL OF	LEAK PROC	EDURE	
STEPS TO TAKE IF SPILLED:				
Using adequate protective equipmer				Pick u
and containerize. Flush area with dil	ute (5%) acetic acid. C	ollect rinsate fo	r sewer or disposal.	
WASTE DISPOSAL:			d in 40 OFP 004 on the best	
This product, if disposed as shippe corrosivity. Consult state or local office			d in 40 CFR 261 on the basi	IS OT IT
corrosivity: consult state or local offic	cials for proper dispose	ii method.		
SECTION	<b>VIII - SPECIAL PRE</b>	CAUTION IN	FORMATION	
VENTILATION REQUIREMENTS Local	except if applied in co	nfined spaces.	where adequate respiratory	
protection is required.		innea opacco,		
PERSONAL PROTECTIVE EQUIPMEN	T RECOMMENDED FOR	NORMAL USE	CONDITIONS:	
Eye protection:	Chemical goggle			
SKIN PROTECTION:	Rubber or plastic	•		
RESPIRATORY PROTECTION:	Respirator with o	rganic vapor ca	rtridge N/A with local exhaust.	
S	ECTION IX - SPECIA	AL PRECAUTI	ONS	
PRECAUTIONS TO BE TAKEN IN HAN	DLING AND STORING:			
Keep container tightly closed when n	ot in use. Store in a dr	v location.		
	SECTION X - TRAI	NSPORTATIO	N	
DOT PROPER NAME:	Corrosivo	e liquid, N.O.S. (	Amine Mixture)	
DOT HAZARD CLASSIFICATION OR D			·	
NDENTIFICATION NUMBER:	UN 1760	)		
PACKAGING GROUP:	III			
LABELS REQUIRED:	Corrosive	9		
SEC	CTION XI - REGULA	TORY INFOR	ATION	
WHMSIS CLASSIFICATION - Class E,				
WHMISIS CLASSIFICATION - Class F	Corrosive			

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.

## S