

MATERIAL SAFETY DATA SHEET

SECTION I

Date of Preparation
June 2011

PRODUCT NAME: ICO Primer SL FC
PRODUCT CLASS: Epoxy Resin, Part A
PRODUCT TYPE: 4,4'Isopropylidenediphenol Epichlorohydrin Resin
D.O.T. CATEGORY: Chemical, NOIBN
ADDRESS: International Coatings
Div. of Milamar Coatings, L.L.C.
311 N.W. 122nd St. Suite 100
Oklahoma City, OK 73114
TELEPHONE: 405-755-8448
EMERGENCY: CHEM TEL 800-255-3924

SECTION II - HAZARDOUS INGREDIENTS

Listed below are the hazardous component(s) as defined in 49 CFR 172 and 29 CFR 1910 which are present in this product and all components which appear on the hazardous substance list of any state:

NONE

SECTION III - PHYSICAL DATA

PHYSICAL STATE: Moderate viscosity, liquid
SPECIFIC GRAVITY: 1.15 at 77°F
DENSITY: 9.6 lbs/gal
PERCENT VOLATILES: 0 at 70°F

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT >200°F (Pensky Martens Closed Cup)
EXTINGUISHING DATA: Foam, Dry Chemical, Carbon Dioxide (CO₂)
NOTE: Toxic fumes will be evolved when this material is involved in a fire. self-contained breathing apparatus should be available for fire fighters. Cool fire-exposed containers with water.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE: High concentration of vapor cause irritation of eyes and respiratory tract.
CHRONIC: Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes, holding eyelid open. **GET MEDICAL ATTENTION.**
SKIN: Wash thoroughly with water while removing contaminated clothing and shoes. Wash clothing before re-use and discard contaminated leather articles. **GET MEDICAL ATTENTION** If effects such as swelling or reddening occur.
INHALATION: Remove to fresh air if effects occur and administer oxygen if necessary. **GET MEDICAL ATTENTION** if effects persist.
INGESTION: **GET MEDICAL ATTENTION IMMEDIATELY** Induce vomiting immediately by depressing back of tongue with a finger or drinking one or more glasses of salt water.

SECTION VI - REACTIVITY DATA

STABILITY: Stable under normal storage conditions.
INCOMPATIBILITY: Avoid bringing into contact with strong oxidizing agents, and strong Lewis or mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS:

CO (Carbon Monoxide) CO₂(Carbon Dioxide) Acid Aldehydes

SECTION VII - SPILL OR LEAK PROCEDURE

IF MATERIAL IS SPILLED: Avoid contact with material. Persons not wearing appropriate protective equipment (see below) should be excluded from the area of spill until clean-up is complete. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank. Remaining Liquid may be taken up on clay, diatomaceous earth or other absorbent and shoveled into disposal containers.

WASTE DISPOSAL METHOD: This product if disposed as shipped is not a hazardous waste as specified under 40 CFR 261. Controlled incineration or buried landfill disposal should be in accordance with all Federal, State & Local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved respiratory protection required in the absence of proper environmental control. For emergencies, a self-contained breathing apparatus, or a full-face respirator is recommended.

VENTILATION: Local, except if applied in enclosed space, in which case proper respiratory equipment (see above) must be worn.

HAND PROTECTION: Impervious gloves, neoprene or rubber.

EYE PROTECTION: Splash proof goggles or safety spectacles with side shields.

OTHER PROTECTIVE EQUIPMENT: Clean Body-covering clothing. Further safety equipment (apron, footwear, etc.) should be used as necessary to prevent contact with material.

SECTION IX - SPECIAL PRECAUTIONS

1. Prevent all skin and eye contact.
2. Avoid breathing vapors.
3. Re-seal part used containers.
4. Ensure that **all** containers are properly labeled to prevent accidental ingestion.
5. Wash with soap and water before eating, drinking, smoking or using toilet facilities.
6. Observe conditions of good industrial hygiene and safe working practice.

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.

MATERIAL SAFETY DATA SHEET

SECTION I

DATE OF PREPARATION

June 2011

PRODUCT NAME: **ICO Primer SL FC**
PRODUCT CLASS: Epoxy Resin Hardener, Part B
PRODUCT TYPE: Modified Polyamine
D.O.T. CATEGORY: UN 2735 Amines, Liquids Corrosive, N.O.S. (1,3-Cyclohexanedimethanamine xylenediamine) 8 PG II
ADDRESS: **International Coatings**
Div. of Milamar Coatings, L.L.C.
311 N.W. 122nd St. Suite 100
Oklahoma City, OK 73114
TELEPHONE: 405-755-8448
EMERGENCY: CHEM TEL 800-255-3924

SECTION II - HAZARDOUS INGREDIENTS

NFPA Hazard Ratings- Health 3, Flammability 1, Reactivity 0

Ingredients	Concentration	Exposure Limit
Meta-xylenediamine	27%	PEL: 0.1mg/m ³ (ceiling) PEL: Skin designation TLV: 0.1 mg/m ³ (ceiling)
Proprietary (non-hazardous)	Balanced	None established

SECTION III - PHYSICAL DATA

APPEARANCE: Clear to light yellow
ODOR: Ammonia like
PHYSICAL PROPERTIES
BOILING POINT: 195°C
MELTING POINT: ND
SPECIFIC GRAVITY: 1.00
VAPOR DENSITY: ND
PERCENT VOLATILES: 0 at 70°F
WATER MISCIBILITY: Slight - 0.1 to 1%

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >200°F (Setaflash Closed Cup)
LFL: No data
UFL: No data
EXTINGUISHING MEDIA: Water, Foam, CO₂, Dry Chemical
UNUSUAL FIRE OR EXPLOSION HAZARDS (Conditions to avoid):
May produce hazardous fumes or hazardous decomposition products
HAZARDOUS DECOMPOSITION PRODUCTS None known to ICO
SPECIAL FIRE FIGHTING PROCEDURES: When fire fighting, wear full protective equipment including self contained breathing apparatus.

SECTION V - HEALTH HAZARD DATA

Test Type	Result	Type	Animal Species	Hazard Rank
LC(50) -	ND			
LC(50) -	ND			

SKIN AND EYE CONTACT: Causes severe skin and eye irritation or burns. May cause permanent visual impairment. Wear protective clothing and chemical goggles. May cause skin sensitization. Avoid contact.

FIRST AID: Immediately flush with water for at least 15 minutes while removing contaminated clothing. Call a physician.

INHALATION: Excessive inhalation can cause respiratory irritation.

FIRST AID: Move to fresh air. If breathing is labored, administer oxygen. If breathing has stopped, administer artificial respiration and seek emergency medical assistance.

ORAL INGESTION: Do not take internally. May cause gastrointestinal burns or ulceration. May cause burns of mouth or throat.

FIRST AID: DO NOT INDUCE VOMITING Give a large quantity of milk or water. Do not give fluids to an unconscious person. Call a physician

OTHER: No carcinogenicity, mutagenicity or teratogenicity effects are known. No effects of chronic exposure or target organ effects are known. No exposure limits have been established for this product as formulated.

SECTION VI - REACTIVITY DATA

INCOMPATIBLE MATERIALS (Materials to avoid): Oxidizers

Product stable under normal conditions

Hazardous polymerization will not occur.

SECTION VII - SPILL OR LEAK PROCEDURE

STEPS TO TAKE IF SPILLED:

Using recommended protective equipment, add dry material to absorb spill (if large spill, first dike to contain).

Pick up and containerize. Flush area with dilute (5%) acetic acid. Collect rinsate for sewer or disposal.

WASTE DISPOSAL:

This product, if disposed as shipped, meets EPA criteria of a hazardous waste as specified in 40 CFR 261 on the basis of its corrosivity. Consult state or local officials for proper disposal methods

SECTION VIII - SPECIAL PRECAUTION INFORMATION

VENTILATION REQUIREMENTS: Local

PERSONAL PROTECTIVE EQUIPMENT RECOMMENDED FOR NORMAL USE CONDITIONS:

EYE PROTECTION: Chemical goggles.

SKIN PROTECTION: Rubber or plastic gloves.

RESPIRATORY PROTECTION: Respirator with organic vapor cartridge N/A with local exhaust.

SECTION IX - SPECIAL PRECAUTIONS

Do not handle or use product until safety precautions recommended in this data sheet have been read and fully understood.

SECTION X - TRANSPORTATION

DOT Proper Shipping Name: Amines, Liquids Corrosive, N.O.S. (1,3-Cyclohexanedimethanamine xylenediamine)

DOT Hazard Classification or Division: 8

Identification Number: UN 2735

Packaging Group: II

Labels Required: Corrosive

SECTION XI - REGULATORY INFORMATION

WHMSIS CLASSIFICATION – Class E, Corrosive

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.