

# MATERIAL SAFETY DATA SHEET

## SECTION I

Date of Preparation  
June 2011

**PRODUCT NAME:** **ICO Rust Guard**  
**PRODUCT CLASS:** Epoxy Resin, Part A  
**PRODUCT TYPE:** 4,4'-Isopropylidenediphenol Epichlorohydrin Resin  
**D.O.T. CATEGORY:** Chemical, NOIBN  
**ADDRESS:** **International Coatings**  
Div. of Milamar Coatings, L.L.C.  
311 N.W. 122<sup>nd</sup> St. Suite 100  
Oklahoma City, OK 73114  
**TELEPHONE:** 405-755-8448  
**EMERGENCY:** CHEM TEL 800-255-3924

## SECTION II - HAZARDOUS INGREDIENTS

Listed below are the hazardous component(s) as defined in 49 CFR 172 and 29 CFR 1910 which are present in this product and all components which appear on the hazardous substance list of any state:

**NONE**

## SECTION III - PHYSICAL DATA

**PHYSICAL STATE:** Moderate viscosity, liquid  
**SPECIFIC GRAVITY:** 1.5-1.8 at 77°F (varies by color)  
**DENSITY:** 12.7-15.2 lbs/gal (varies by color)  
**SOLUBILITY:** Negligible  
**ODOR:** Slight aromatic  
**pH:** N.A.  
**PERCENT VOLATILES** 0 at 70°F

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT** 480°F (Pensky Martens Closed Cup)  
**EXTINGUISHING DATA:** Foam, Dry Chemical, Carbon Dioxide (CO<sub>2</sub>)  
**FLAMMABILITY CLASSIFICATION:** Combustible Liquid, Class IIIB  
**LOWER EXPLOSIVE LIMITS:** N/A  
**FIRE FIGHTING INSTRUCTIONS:** Use self-contained breathing apparatus and full protective equipment.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Fumes, CO, CO<sub>2</sub>, acrid smoke, phenolics, aldehydes

## SECTION V - HEALTH HAZARD DATA

### EFFECTS OF OVEREXPOSURE:

**ACUTE:** High concentration of vapor cause irritation of eyes and respiratory tract.  
**CHRONIC:** Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.  
**EYE:** Will cause moderate eye irritation  
**INHALATION:** Unlikely except at elevated temp; may cause allergic reaction  
**SKIN ABSORPTION:** Not likely  
**SKIN CONTACT:** Possible skin irritant  
**INGESTION:** Will cause illness  
**EMERGENCY AND FIRST AID PROCEDURES:**  
**EYES:** Flush with water for at least 15 minutes, holding eyelid open. **GET MEDICAL ATTENTION.**  
**SKIN:** Wash thoroughly with water while removing contaminated clothing and shoes. Wash clothing before re-use and discard contaminated leather articles. **GET MEDICAL ATTENTION** if effects such as swelling or reddening occur.  
**INHALATION:** Remove to fresh air if effects occur and administer oxygen if necessary. **GET MEDICAL ATTENTION** if effects persist.  
**INGESTION:** **DO NOT INDUCE VOMITING** Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if victim is conscious. **GET MEDICAL ATTENTION IMMEDIATELY.**

**SECTION VI - REACTIVITY DATA**

**STABILITY:** Stable under normal storage conditions.  
**INCOMPATIBILITY:** Avoid bringing into contact with strong acids, bases and oxidizers  
**HAZARDOUS DECOMPOSITION PRODUCTS:** See Sect. IV

**SECTION VII - SPILL OR LEAK PROCEDURE**

**IF MATERIAL IS SPILLED:** Avoid contact with material. Persons not wearing appropriate protective equipment (see below) should be excluded from the area of spill until clean-up is complete. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank. Remaining Liquid may be taken up on clay, diatomaceous earth or other absorbent and shoveled into disposal containers.

**WASTE DISPOSAL METHOD:** This product, if disposed as shipped, is not a hazardous waste as specified on 40CFR261. Controlled incineration is preferred method of disposal.

**SECTION VIII - SPECIAL PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** No respiratory protection should be needed unless applied in a confined space, in which case a NIOSH-approved positive-pressure supplied-air respirator should be used.

**VENTILATION:** Local

**HAND PROTECTION:** Impervious gloves, neoprene or rubber.

**EYE PROTECTION:** Splash proof goggles or safety spectacles with side shields.

**OTHER PROTECTIVE EQUIPMENT:** Clean Body-covering clothing. Further safety equipment (apron, footwear, etc.) should be used as necessary to prevent contact with material.

**SECTION IX - SPECIAL PRECAUTIONS**

1. Prevent all skin and eye contact.
2. Avoid breathing vapors.
3. Re-seal part used containers.
4. Ensure that all containers are properly labeled to prevent accidental ingestion.
5. Wash with soap and water before eating, drinking, smoking or using toilet facilities.
6. Observe conditions of good industrial hygiene and safe working practice.

**SECTION X – REGULATORY INFORMATION**

**WHMIS INFORMATION – D2B– skin sensitizer**

**THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.**

# MATERIAL SAFETY DATA SHEET

## SECTION I

DATE OF PREPARATION

June 2011

**PRODUCT NAME:** **ICO Rust Guard**  
**PRODUCT CLASS:** Epoxy Resin Hardener, Part B  
**PRODUCT TYPE:** Modified amine  
**D.O.T. CATEGORY:** UN 1760 Corrosive liquid, N.O.S.(Amine Mixture) 8 PG III  
**ADDRESS:** **International Coatings**  
Div. of Milamar Coatings, L.L.C.  
311 N.W. 122<sup>nd</sup> St. Suite 100  
Oklahoma City, OK 73114  
**TELEPHONE:** 405-755-8448  
**EMERGENCY:** CHEM TEL 800-255-3924

## SECTION II - HAZARDOUS INGREDIENTS

**NFPA Hazard Ratings-** Health 2, Flammability 1, Reactivity 1

Ingredients	CAS#	Max.-Content	Exposure Limit
Modified Polyamines	Proprietary	55%	none assigned
Nonyl Phenol	84852-15-3	15%	none assigned
Aminoethyl Piperazine	140-31-8	10%	none assigned
Benzyl Alcohol	100-51-6	25%	none assigned

## SECTION III - PHYSICAL DATA

**PHYSICAL STATE:** Low Viscosity, amber color  
**SPECIFIC GRAVITY:** 1.0 at 77°F  
**DENSITY:** 8.5 lbs./gal at 77° F  
**ODOR:** Amine  
**VAPOR PRESSURE:** Less than 1 mm Hg @ 68°F  
**PERCENT VOLATILES:** 0 AT 70°F

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** >200°F (Setaflash Closed Cup)  
**LFL:** No data  
**UFL:** No data  
**Extinguishing Media:** Water fog, Alcohol Foam, CO<sub>2</sub>, Dry Chemical  
**SPECIAL FIRE FIGHTING PROCEDURES:** Use a positive pressure, self-contained breathing apparatus. Wear full protection coating.  
**Note:** Will burn under right conditions of heat and oxygen supply.

## SECTION V - HEALTH HAZARD DATA

**PERMISSIBLE EXPOSURE LEVEL** None established  
**EFFECTS OF OVER EXPOSURE:**  
**INHALATION** May cause nasal irritation, central nervous system depression or lung injury.  
**EYES** This product can cause chemical burns to eyes. Eye damage may be irreversible.  
**SKIN** May be corrosive or highly irritating to the skin. Repeated contact may cause sensitization and/or dermatitis.  
**FIRST AID:**  
**EYES** Flush with water for at least 15 minutes. **GET MEDICAL ATTENTION**  
**SKIN** Wash thoroughly with water. Remove contaminated clothing and shoes. Wash clothing before re-use. Get medical attention if effects such as swelling or reddening occur.  
**INHALATION** Remove to fresh air if effects occur and administer oxygen if necessary. **GET MEDICAL ATTENTION.**  
**INGESTION** **GET MEDICAL ATTENTION IMMEDIATELY** Do not induce vomiting unless directed by physician.

## SECTION VI - REACTIVITY DATA

**STABILITY:** Stable under normal storage conditions.

**INCOMPATIBILITY:** Avoid bringing into contact with strong oxidizing agents, and strong Lewis or Mineral acids, bases

**HAZARDOUS DECOMPOSITION PRODUCTS:**

CO (Carbon Monoxide)

CO<sub>2</sub> (Carbon Dioxide)

Acids

Aldehydes

**SECTION VII - SPILL OR LEAK PROCEDURE****STEPS TO TAKE IF SPILLED:**

Using adequate protective equipment, add dry material to absorb spill (if large spill, first dike to contain). Pick up and containerize. Flush area with dilute (5%) acetic acid. Collect rinsate for sewer or disposal.

**WASTE DISPOSAL:**

Product is classified as "corrosive" and as such must be disposed of as a hazardous waste according to Federal, State and Local regulations.

**SECTION VIII - SPECIAL PRECAUTION INFORMATION**

**VENTILATION REQUIREMENTS:** Local, except in confined spaces, e.g., tanks, in which case proper respiratory equipment (see below) is required.

**PERSONAL PROTECTIVE EQUIPMENT RECOMMENDED FOR NORMAL USE CONDITIONS:**

**EYE PROTECTION:** Chemical goggles.

**SKIN PROTECTION:** Rubber or plastic gloves.

**RESPIRATORY PROTECTION:** Respirator with organic vapor cartridge N/A with local exhaust.

**SECTION IX - SPECIAL PRECAUTIONS****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:**

Keep container tightly closed when not in use. Store in a dry location.

**SECTION X - TRANSPORTATION**

**DOT Proper Shipping Name:** Corrosive liquid, N.O.S (Amine Mixture)

**DOT Hazard Classification or Division:** 8

**Identification Number:** UN 1760

**Packaging Group:** III

**Labels Required:** Corrosive

**SECTION XI – REGULATORY INFORMATION**

**WHMSIS CLASSIFICATION** – Class E, Corrosive

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION INTERNATIONAL COATINGS CONSIDERS TO BE ACCURATE. NO WARRANTY EXPRESSED OR IMPLIED IS INTENDED.