

PRODUCT NAME: **SUPERCOAT 550 WB URETHANE, PART A**

PAGE: 1

## MATERIAL SAFETY DATA SHEET

### 24 HOUR EMERGENCY ASSISTANCE

CHEM TEL: 1-800-255-3924

### GENERAL ASSISTANCE

TELE-TECH: 405-755-8448

**HEALTH:** 1

#### HAZARD RATING

**FIRE:** 0

LEAST = 0

SLIGHT = 1

MODERATE = 2

**REACTIVITY:** 0

HIGH = 3

EXTREME = 4

### SECTION I

**PRODUCT:** SUPERCOAT 550 WB URETHANE, PART A

CHEMICAL NAME: POLYACRYLATE RESIN

CHEMICAL FAMILY: POLYACRYLATE RESIN

PRODUCT DESCRIPTION: WATER BORNE RESIN DISPERSION

### SECTION II-A

#### PRODUCT / INGREDIENT

<u>No.</u>	<u>COMPOSITION</u>	<u>CAS NUMBER</u>	<u>PERCENT</u>
------------	--------------------	-------------------	----------------

THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENTS

### SECTION II-B

#### ACUTE TOXICITY DATA

<u>No.</u>	<u>ACUTE ORAL LD50</u>	<u>ACUTE DERMAL LD50</u>	<u>ACUTE INHALATION LC50</u>
------------	------------------------	--------------------------	------------------------------

THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENTS AS DEFINED UNDER THE CRITERIA OF THE FEDERAL OSHA COMMUNICATION STANDARD 29 CFR 1910.1200.

### SECTION III

#### HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910-1200).

**EYE CONTACT:** EYE CONTACT CAN CAUSE MODERATE IRRITATION, WITH REDNESS, TEARING AND BLURRED VISION. PROLONGED CONTACT MAY CAUSE CORNEAL INFLAMMATION WHICH IS USUALLY REVERSIBLE..

**SKIN CONTACT:** PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, REDDENING, SCALING AND DERMATITIS.

**INHALATION:** PROLONGED OR REPEATED EXPOSURE TO VAPOR CAN CAUSE IRRITATION TO THE NASAL PASSAGES, THROAT, DIZZINESS AND HEADACHES. HIGH CONCENTRATION MAY RESULT IN NARCOSIS.

**INGESTION:** CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA

**AGGRAVATED MEDICAL CONDITIONS:** NONE KNOWN

### SECTION IV

#### OCCUPATIONAL EXPOSURE LIMITS

	OSHA		ACGIH		OTHER
No.	PEL/TWA	PEL/CEILING	TLV/TWA	TLV/STEL	

NOT ESTABLISHED FOR THE PRODUCT

### SECTION V

#### EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** CHECK FOR AND REMOVE CONTACT LENSES. IMMEDIATELY FLUSH EYES WITH RUNNING WATER FOR AT LEAST 15 MINUTES, KEEPING EYELIDS OPEN. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

PRODUCT NAME: **SUPERCOAT 550 WB URETHANE, PART A**

PAGE: 2

**SKIN CONTACT:** WASH GENTLY AND THOROUGHLY THE CONTAMINATED SKIN WITH RUNNING WATER AND NON-ABRASIVE SOAP. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

**INHALATION:** NO KNOWN EFFECT ACCORDING TO OUR DATABASE.

**INGESTION:** **DO NOT INDUCE VOMITING.** HAVE A CONSCIOUS PERSON DRINK SEVERAL GLASSES OF WATER OR MILK. SEEK IMMEDIATE MEDICAL ATTENTION.

---

## SECTION VI

## SUPPLEMENTAL HEALTH INFORMATION

---

CONTACT A POISON CONTROL CENTER FOR ADDITIONAL TREATMENT INFORMATION.

---

## SECTION VII

## PHYSICAL DATA

---

BOILING POINT (°F): 212F (100C) SPECIFIC GRAVITY (H<sub>2</sub>O = 1): 1.06

VAPOR PRESSURE (mm Hg @ 20°C): 29.33 MM HG @ 68F

SOLUBILITY (IN WATER): DISPERSIBLE

VAPOR DENSITY (AIR = 1): .569 (AIR=1)

EVAPORATION RATE (N-BUTYL ACETATE = 1): .07

APPEARANCE AND ODOR: LIGHT STRAW COLORED LIQUID, AMMONIA ODOR

---

## SECTION VIII

## FIRE AND EXPLOSION HAZARDS

---

FLASH POINT AND METHOD: GREATER THAN 250 F (121 C) SETAFLASH

FLAMMABLE LIMITS /% VOLUME IN AIR:

UPPER EXPLOSIVE LIMIT (UEL) (%) 25

LOWER EXPLOSIVE LIMIT (LEL) (%) 16

**EXTINGUISHING MEDIA:** WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM

**SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:** FULL EMERGENCY EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING SHOULD BE WORN BY THE FIRE - FIGHTERS. USE COLD WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS TO MINIMIZE RISK OF RUPTURE. MATERIAL SUPPORTS COMBUSTION. DURING A FIRE, IRRITATING AND TOXIC GASES SUCH AS CARBON MONOXIDE MAY BE GENERATED BY THERMAL DECOMPOSITION OR COMBUSTION. SEE SECTION VIII. DO NOT SPRAY FIRE DIRECTLY. A SOLID STREAM DIRECTED INTO THE HOT BURNING LIQUID COULD CAUSE FROTHING.

---

## SECTION IX

## REACTIVITY

---

**STABILITY:** THIS IS A STABLE MATERIAL

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR

**CONDITIONS AND MATERIALS TO AVOID:** NONE FOUND

**HAZARDOUS DECOMPOSITION PRODUCTS:** BY FIRE: CO<sub>2</sub>, CO, AND OTHER ALIPHATIC FRAGMENTS.

---

## SECTION X

## EMPLOYEE PROTECTION

---

EYE PROTECTION REQUIREMENTS: SAFETY GLASSES OR GOGGLES ARE RECOMMENDED

SKIN PROTECTION REQUIREMENTS: IMPERMEABLE GLOVES ARE RECOMMENDED

RESPIRATORY/VENTILATION REQUIREMENT: GENERAL DILUTION VENTILATION THAT MAINTAINS VAPOR LEVELS BELOW THE APPROPRIATE EXPOSURE LIMIT IS RECOMMENDED. RESPIRATORY PROTECTION IS NOT REQUIRED WHILE HANDLING THIS PRODUCT UNDER NORMAL CONDITIONS OF USE (SEE SECTION IV FOR THE TYPE OF RESPIRATORY PROTECTION NECESSARY IN A FIRE SITUATION). IF THIS PRODUCT IS USED IN CONJUNCTION WITH OTHER MATERIALS, CONSULT THE APPROPRIATE MATERIAL SAFETY DATA SHEETS FOR RECOMMENDED RESPIRATORY PROTECTION.

ADDITIONAL MEASURES SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE EASILY ACCESSIBLE TO THE WORK AREA. EMPLOYEE TRAINING AND EDUCATION IN THE SAFE HANDLING AND USE OF THIS PRODUCT IS ESSENTIAL.

PRODUCT NAME: **SUPERCOAT 550 WB URETHANE, PART A**

PAGE: 3

---

## SECTION XI

## ENVIRONMENTAL PROTECTION

---

### SPILL OR LEAK PROCEDURES:

COVER SPILL WITH ABSORBENT MATERIAL, SUCH A SAND, SWEEPING COMPOUND OR DIATOMACEOUS EARTH; COLLECT MATERIAL FOR DISPOSAL. WASH SPILL AREA WITH HOT WATER.

WASTE DISPOSAL METHOD.....WASTE MUST BE DISPOSED OF OR INCINERATED IN COMPLIANCE WITH FEDERAL, STATE OR LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

---

## SECTION XII

## SPECIAL PRECAUTIONS

---

GROUND ALL TRANSFER EQUIPMENT. TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE. HANDLE AS AN INDUSTRIAL CHEMICAL. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. PRACTICE GOOD CAUTION AND PERSONAL CLEANLINESS TO AVOID SKIN AND EYE CONTACT. HOLD BULK STORAGE UNDER NITROGEN BLANKET. STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

---

## SECTION XIII

## TRANSPORTATION REQUIREMENTS

---

**TECHNICAL SHIPPING NAME:** POLYACRYLATE DISPERSION

**FREIGHT CLASS BULK:** SYNTHETIC RESIN

**FREIGHT CLASS PACKAGE:** RESIN, COAL TAR OR PETROLEUM

**PRODUCT LABEL:** WATERBORNE URETHANE

DOT DOMESTIC SURFACE

HAZARD CLASS OR DIVISION.....NON-REGULATED

IMO / IMDG CODE (OCEAN)

HAZARD CLASS DIVISION NUMBER....NON-REGULATED

ICAO / IATA (AIR)

HAZARD CLASS DIVISION NUMBER.....NON-REGULATED

---

## SECTION XIV

## OTHER REGULATORY CONTROLS

---

NOT MEANT TO BE ALL-INCLUSIVE. SELECTED REGULATIONS PRESENTED.

- A. SARA TITLE III SECTION 311/312 HAZARDS: NON-HAZARDOUS UNDER 311/312
- B. SARA TITLE III SECTION 313: TOXIC CHEMICALS: NONE
- C. WHMIS CLASSIFICATION:
- D. TSCA STATUS: ON TSCA INVENTORY
- E. OSHA HAZARD COMM. STD.:

ANIMAL TOXICITY DATA.....NO ANIMAL TOXICITY INFORMATION AVAILABLE

FEDERAL REGULATORY INFORMATION...

OSHA STATUS....THIS PRODUCT IS NOT HAZARDOUS UNDER THE CRITERIA OF THE FEDERAL OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

TSCA STATUS... ON THE TSCA INVENTORY

CERCLA REPORTABLE QUANTITY NONE

OTHER REGULATORY INFORMATION

COMPONENT NAME

/CAS NUMBER

POLYACRYLATE RESIN

APPROX. 60-70 %

PA3, NJ4

NJ4=NEW JERSEY OTHER-INCLUDED IN 5 PREDOMINANT INCREDIENTS >1%

PA3=PENNSYLVANIA NON-HAZARDOUS PRESENT AT 3% OR GREATER.

PRODUCT NAME: **SUPERCOAT 550 WB URETHANE, PART A**

PAGE: 4

RCRA STATUS....IF DISCARDED IN ITS PURCHASED FORM, THIS PRODUCT WOULD NOT BE BE A HAZARDOUS WASTE EITHER BY LISTING OR BY CHARACTERISTIC. HOWEVER, UNDER RCRA, IT IS THE RESPONSIBILITY OF THE PRODUCT USER TO DETERMINE AT THE TIME OF DISPOSAL, WETHER A MATERIAL CONTAINING THE PRODUCT OF DERIVED FROM THE PRODUCT SHOULD BE CLASSIFIED AS A HAZARDOUS WASTE. (40CFR 261.20-24)

---

## **SECTION XV**

## **STATE REGULATORY INFORMATION**

---

NONE KNOWN

CA = CALIFORNIA HAZ. SUBST. LIST; CA65 = CALIFORNIA SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT LIST; CT = CONNECTICUT TOX. SUBST. LIST; FL = FLORIDA SUBST. LIST; IL = ILLINOIS TOX. SUBST. LIST; LA = LOUISIANA HAZ. SUBST. LIST; MA = MASSACHUSETTS SUBST. LIST; ME = MAINE HAZ. SUBST. LIST; MN = MINNESOTA HAZ. SUBST. LIST; NJ = NEW JERSEY HAZ. SUBST. LIST; PA = PENNSYLVANIA HAZ. SUBST. LIST; RI = RHODE ISLAND HAZ. SUBST. LIST.  
POLYESTER RESIN

---

## **SECTION XVI**

## **SPECIAL NOTES**

---

NEW MSDS.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, MILAMAR COATINGS, INC. MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MILAMAR COATINGS, INC. ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

---

DATED PREPARED: SEPTEMBER 13, 2011  
PREPARED BY: MILAMAR COATINGS, INC.  
311 NW 122<sup>ND</sup> ST, STE 100  
OKLAHOMA CITY, OK 73114