

 Dovicion Doto		Drint Data	00/07/10		
Revision Date:	08/12	Print Date:	08/27/12		
Version 3.0		MSDS Identification:	1000CS - Part A	Epoxy Resin	

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name :	1000CS - Part A
Product Use Description :	Epoxy Resin
Company :	Protective Floorings and Linings A Division of Milamar Coatings, LLC 311 N.W. 122nd St, Suite 100 Oklahoma City, OK 73114
Telephone :	405-755-8448
Emergency Telephone Number:	ChemTel 800-255-3924 or 813-248-0585 (International)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients 1	% Wt.	Symbol	CAS No.	EC No.	R-phrases
Epoxy resin(number average molecular weight	40-50	Xi,N	25068-38-6	500-033-5	36/38-43-51/53
<=700)					
2,3-Epoxypropyl O-tolyl Ether	10-15	Xn, N	2210-79-9	218-645-3	38-68-43-51/53
Ethylbenzene	<1	F, Xn	100-41-4	202-849-4	11-20
Iron Oxide	0-5	-	1309-37-1	215-168-2	-
Silica (Quartz)	1-10	-	14808-60-7	238-878-4	-
Titanium Oxide	0-10	-	13463-67-7	236-675-5	-

3. HAZARDS INFORMATION

Emergency Overview Harmful If Swallowed Skin Sensitization May Cause Pulmonary Sensitization Eye Irritation Skin Irritation

4. FIRST AID MEASURES

Inhalation	:	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
Skin Contact	:	Remove contaminated clothing / shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until thoroughly cleaned. Contaminated leather articles, including shoes, cannot be decontaminated and should be destroyed to prevent reuse.

VIALEITAL	Safety Data Revision Date: Version 3.0	Sheet 08/12	Print Date: MSDS Identification:	08/27/12 1000CS - Part A	Epoxy Resin
	Eye Contact		:	Flush eyes with plenty c medical attention.	of water for 15 minutes while holding eyelids open. Get
	Ingestion		:	Do not induce vomiting. prevent aspiration. Get	If vomiting occurs spontaneously, keep head below hips to medical attention.
	NOTES TO PHYS Symptoms	SICIAN	:		e. Skin sensitization (allergy) may be evidenced by rashes, sensitization (e.g., allergy, asthma) may be evidenced by s of breath and cough.
	Treatment		:	should be induced with aspiration. If symptoms	kg has been ingested and vomiting has not occurred, emesis supervision. Keep victim's head below hips to prevent such as loss of gag reflex, convulsions or unconsciousness istric lavage using a cuffed endotracheal tube should be
5. FIRE-FIG	HTING MEASUF	RES			
	Suitable Extinguis	shing Media	:	Use water fog, "alcohol	foam", dry chemical or carbon dioxide.
	Specific Hazards	During Fire	Fighting :	Material will not burn un	less preheated.
	Special Protective	e Equipment	For Fire Fighters:		re space without full bunker gear (helmet with face shield, d rubber boots). Including a positive pressure NIOSH I breathing apparatus
	Personal Precauti	ions	:		eadily ignitable. Use cautious judgment when cleaning up iks, if possible without personal risk.
	Environmental Pre	ecautions	:	Dike and contain. Contain	ain run-off and dispose of properly.
	Clean-up Methods	s - Small Sp	illage :	Take up with an absorb	ent material and dispose of properly.
	Clean-up Methods	s - Large Sp	illage :	with an absorbent such	ucks or pump to storage / salvage vessels. Soak up residue as clay, sand or other suitable material; place in non-leaking sposal. Flush area with water to remove trace residue.
	Additional advice		:		exposures to the general public or environment occurs or is tion 13 for information on disposal.
6. ACCIDEN	ITAL RELEASE	MEASUR	ES :	(See Section 15 For Re	gulatory Information).
	Protect People		:	Use appropriate safety e	ecessary and unprotected personnel from entering the area equipment. For additional information, refer to Section 8, rsonal Protection. Refer to Section 7, Handling, for additional s.
	Protect The Enviro				ne soil, ditches, sewers, waterways and / or groundwater.

Material Safety	Data	Sheet
-----------------	------	-------

	sion Date: sion 3.0	08/12 MSDS I	Print Date: dentification:	08/27/12 1000CS - Part A	Epoxy Resin
Clear	nup			containers. Remove res recommended for clean handling practices for th	ch as sand. Collect in suitable and properly labeled sidual with soap and hot water. Solvents are not up unless the recommended exposure guidelines and safe e specific solvent are followed. Consult appropriate solvent mation and exposure guidelines
7. Handling an	D STORAG	iΕ			
Hand	ling			possibly cause pulmona emptied, can contain ha soap and water before e facilities. Launder conta	htly toxic if swallowed. May cause skin sensitization. May ry sensitization. Containers, even those that have been zardous product residues. Minimize skin contact. Wash with eating, drinking, smoking, applying cosmetics, or using toile! iminated clothing before using. Contaminated leather articles, be decontaminated and should be destroyed to preven!
Stora	ge			Store in a cool, dry place high temperatures.	e with adequate ventilation. Keep away from open flames and

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Protective Measures	:	Wear appropriate respirator and protective clothing
Engineering Measures	:	Use ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for emergency use.
Eye Protection	:	Avoid contact with eyes. Wear chemical goggles if there is potential contact with eyes.
Skin And Body Protection	:	Avoid prolonged or repeated contact with skin. Wear chemical-resistant gloves and other clothing as required to minimize contact.
Respiratory Protection	:	Avoid breathing vapor or mists. Use a NIOSH-approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, Use either a full-face, atmosphere-supplying respirator or air purifying respirator for organic vapors

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical State	:	Liquid.
Odor	:	Yellow.
Flash Point	:	> 93.33 degrees C (>199.99 degrees F) (Setaflash)
Vapor Pressure	:	Negligible.
Relative Density	:	1.14.
Relative Vapor Density	:	> 1.
Solubility In Water	:	Negligible.

Protective Floorings Linings

Revision Date:	08/12	Print Date:	08/27/12	
Version 3.0		MSDS Identification:	1000CS - Part A	Epoxy Resin

10. STABILITY AND REACTIVITY

Materials To Avoid	:	Can react vigorously with strong oxidizing agents, strong lewis or mineral acid, and strong mineral and organic bases, especially primary and secondary aliphatic amines. Reacts with considerable heat release with some curing agents.
Hazardous Decomposition Products	:	Carbon monoxide, aldehydes, and acids may be formed during combustion.
Hazardous Reactions	:	Hazardous polymerization will not occur. Stable under normal use conditions.

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity	:	Expected to be of low toxicity, LD50 > 2000 mg/kg.
Acute Dermal Toxicity	:	Expected to be of low toxicity, LD50 > 2000 mg/kg.
Inhalation	:	Not expected to be a relevant route of exposure, however, under conditions where exposure to vapors or mists is possible, could cause respiratory tract irritation. May possibly cause pulmonary sensitization.
Skin	:	May be mildly irritating to the skin. Prolonged or repeated liquid contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis. May cause skin sensitization.
Eyes	:	May be irritating to the eyes.
Ingestion	:	May be slightly toxic and may be harmful if swallowed.
Aggravated Medical Condition	:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product. Pre-existing skin or lung allergies may increase the chance of developing increased allergy symptoms from exposure.

12. ECOLOGICAL INFORMATION		
Biodegradability	:	This section will be updated as ecological reviews are completed.
Toxicity To Fish	:	This section will be updated as ecological reviews are completed.
13. DISPOSAL CONSIDERATIONS Product Disposal	:	If this material becomes a waste, it would not be a hazardous waste RCRA criteria (40 CFR 261). Place in an appropriate disposal facility in compliance with local and federal regulations.

14. TRANSPORT INFORMATION

Material Safety Data Sheet

Revision Date Version 3.0	e: 08/12	Print Date: entification:		Epoxy Resin	
CFR	Proper Shipping Name Class UN / ID No. Packing Group	: : :	not regulated		
15. REGULATORY INFO	RMATION				
TSCA		:	All components listed.		
EINECS		:	All components are listed of	or exempt.	
DSL		:	All components listed.		
KECI (KR)		:	All components listed.		
PICCS (PH)		:	All components listed.		
ENCS (JP)		:	All components listed.		
INV (CN)		:	All components listed.		
AICS		:	All components listed.		
Bisphenol A /	RCLA Hazardous Substanc Epichlorohydrin Resin LYCIDYLETHER	es (40 CFR 302 : :	2) No RQ No RQ		
Section 311/3	312	:	Acute Health Hazard		
(40 CFR 372.6 Bisphenol A /	ergency Planning and Com 55) - Supplier Notification R Epichlorohydrin Resin LYCIDYLETHER		No De minimis Concentratio		
U.S. EPA Eme (40 CFR 355, Bisphenol A /	ergency Planning and Com	·munity Right-To	No De minimus Concentrat p-Know Act (EPCRA) SAR Threshold Planning Quani : Threshold Planning Quani :	RA Title III Section 302 Extremely Hazardous Si	ubstance
Bisphenol A /	Epichlorohydrin Resin LYCIDYLETHER	:	Reportable Quantity : Reportable Quantity	: No RQ Not Listed	
Bisphenol A / O-CRESYL G	ight-To-Know Chemical Lis Epichlorohydrin Resin LYCIDYLETHER	:	Not Listed Not Listed		

Additional Components Not Found in Section ::

Components	CAS - No.	Concentration	Remarks
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed

Pennsylvania Right-To-Know Chemical List

Revision Date:	08/12	Print Date:	08/27/12	
Version 3.0		MSDS Identification:	1000CS - Part A	Epoxy Resin

Bisphenol A / Epichlorohydrin Resin	:	Not Listed
O-CRESYL GLYCIDYLETHER	:	Not Listed

Additional Components Not Found In Section 2:

Components	CAS - No.	Concentration	Remarks
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed

Massachusetts Right-To-Know Chemical List.Bisphenol A / Epichlorohydrin Resin:O-CRESYL GLYCIDYLETHER:Not Listed

Additional Components Not Found In Section 2:

Components	CAS - No.	Concentration	Remarks
Phenyl Glycidyl Ether	122-60-1	< 5 PPM	Not Listed

U.S. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) Additional Components Not Found in Section 2.

Components	Concentration	Concentration	Remarks	Value
Phenyl Glycidyl Ether	< 5 PPM	U.S. California Safe Drinking Water And Toxic Enforcement Act (Proposition 65).	Not Listed	Listed: October 1, 1990
HMIS Rating Health : Flammability : Reactivity :	: 1			
Canadian Classification	:	B3: Combustible liquids; D2B: Toxic r materials causing other effects	naterials causing other effects; D	2A: Very toxic
Risk Phrase(s)	:	Combustible liquid. Possible risk of erreversible effects. Irritating to eyes and skin. N cause sensitisation by skin contact		es and skin. May
Precautionary and First Aid Measure(s)	:	Wear Suitable protective clothing,glov In case of contact with eyes, rinse im adivce. After contact with skin, wash	mediately with plenty of water and	l seek medical
Other information	:	None		

16. OTHER INFORMATION

The information contained above is given in good faith based on the best data available at this time. No warranty, expressed or implied is made. User assumes full responsibility for determining appropriate use and application of the product. Consult PF&L, Inc. for further information.

Prepared By	: Protective Floorings and Linings.	Protective Floorings and Linings. EH&S Product Safety Department	
	1		
	Classified according to:	*29 CFR 1910,1200,1915,1916,1917	
		*Mass, right-to-know law(ch. 40,M.G.LO 111F)	
		*Canadian WHMIS regulations	
		*67/548/EEC(29th Adaption) and 99/45EC	
		*Worksafe Austialia (NOHSC: 1008(1999))	